

GYP GRIP 40

HEAVY DUTY CONSTRUCTION ADHESIVE

PRODUCT NAME

Gyp Grip 40 - Heavy Duty Construction Adhesive

MANUFACTURER

Everkem Diversified Products
 120 Regent Drive, Winston Salem, NC 27103
 PH: 1-800-638-3160 | FAX: (336) 661-7969

PRODUCT DESCRIPTION

Gyp Grip 40 is a heavy-duty acrylic-based construction adhesive, formulated to adhere drywall to wood and steel studs, gypsum board to gypsum board. Gyp Grip 40 provides a fast grab for easy drywall installation and high-strength adhesion, reducing nailing and the use of mechanical fasteners up to 50%.

APPLICATIONS

- Wood and steel studs
- Rafters
- Drywall and concrete

ADVANTAGES

- Tested to ASTM-C557
- Reduces fastener use up to 50%
- Reduces nail pops
- Dampens sound
- High-strength adhesion

LIMITATIONS

Not recommended for: Exterior wall construction, extruded polystyrene foam, polystyrene or ABS plastic panels, and ceiling tiles and acoustical panels.

AVAILABLE COLORS

Gyp Grip 40 is available in Tan.

TECHNICAL DATA

TYPICAL PHYSICAL PROPERTIES

Typical Uncured Properties

Chemistry:	Acrylic latex
Uncured State:	Glossy paste
Odor:	Low acrylic odor
Application Temperature:	45°F to 110°F (7.2°C to 43.3°C)
Tooling Time:	30 minutes
Full Cure Time:	Up to 7 days
Shelf Life:	18 months

Typical Cured Properties
 Curing conditions of 75°F (24°C) and 50% relative humidity)

Cured State:	Firm paste
ASTM-C557:	Meets ASTM-C557 "Standard Specification for Adhesives Fastening Wallboard to Wood Framing"
Service Temperature:	Up to 120°F (49°C)
Paintability:	Paintable with latex paint after 2 hours; with oil-based paint after 24+ hours
Freeze/Thaw:	Excellent, exceeds 5 cycles
V.O.C. Content:	32 g/L

GYP GRIP 40

HEAVY DUTY CONSTRUCTION ADHESIVE

TECHNICAL DATA [CONT]

APPLICABLE STANDARDS & SPECIFICATIONS

SPECIFIED DIVISIONS

- Section 07 92 00 - Joint Sealants
- Section 09 20 00 - Plaster and Gypsum Board

APPLICABLE STANDARDS/SPECIFICATIONS

- ASTM-C557 - Standard Specification for Adhesives Fastening Wallboard to Wood Framing

ECOSEAL STANDARDS

- V.O.C. Content: 32 g/L

INSTALLATION

SURFACE PREPARATION

Surfaces should be clean of any debris or material that may prevent or deter adhesion. Such debris includes, but is not limited to: dirt, frost, loose particles, existing sealants, grease, oils, rust, etc. Ensure that any assemblies are structurally sound.

APPLICATION

1. Cut and pre-fit materials before applying the product and installing.
2. Cut nozzle to desired bead size. Apply adhesive directly onto studs and plates starting approximately 5 inches from the top and bottom of where each panel is positioned on the stud and plates.
3. Apply two additional parallel beads of adhesive on the stuff at the joint where two drywall pieces meet.
4. Position drywall and press firmly to the stud. For best results, complete positioning of drywall within 15 minutes of product application.
5. Follow the fastening schedule for drywall applications using an adhesive as stated by applicable code bodies and/or as stated in the Gypsum Association manual.
6. For best results, boards should not be finished until the adhesive has fully cured.
7. Product will begin to set within a few hours, dependent on ambient conditions. Allow up to 7 days for a full cure resulting in maximum adhesion.

CLEANUP

Excess caulk should be cleaned off tools and nonporous surfaces while it is in the uncured state using water and a dry cloth or paper towels. Excessive amounts may require the use of a solvent such as acetone or mineral spirits. The cured compound should be cut away.

AVAILABILITY

Gyp Grip 40 and other Everkem products are available from stocking distributors nationwide or direct from the manufacturer. For the name and telephone number of the nearest Everkem representative, call the number below or visit www.everkemproducts.com

PACKAGING OPTIONS

PACKAGING OPTIONS			
Part #	Description	Packaging	Color
GG40-28	Gyp Grip 40 - 28 Fl. Oz. (828.06mL) Tube	12 tubes/case	Tan

MAINTENANCE

Inspect sealant and strength of adhesion of application at a minimum of every five years. If sealant or bond of sealant is damaged, completely remove or cut away sealant in the damaged area, clean surface, and reapply sealant.

GYP GRIP 40

HEAVY DUTY CONSTRUCTION ADHESIVE

TECHNICAL SERVICES

Everkem representatives are available to assist you in selecting the sealant or adhesive appropriate for your application. For further assistance contact your local Everkem Diversified Products representative, call our corporate office at 1-800-638-3160, or contact us via our website at www.everkemproducts.com

WARRANTY

Everkem Diversified Products warrants this product's performance provided it is properly stored and applied within 18 months. If when applied as directed this material proves to be defective, return the remaining product and proof of purchase for refund or replacement of product exclusive of labor or cost of labor. This is the sole and exclusive remedy for defects of product failure. The determination of eligibility for this warranty shall be made at the sole discretion of Everkem Diversified Products and any decision made shall be final. This warranty is in lieu of any other warranties, expressed or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose, and in no instance will Everkem Diversified Products be liable for damages in excess of the purchase price, except where such exclusion or limitation is prohibited by state law. Users must read and follow the directions of the current Technical Data Guide and SDS prior to product use. The user determines the suitability of the product intended for use and assumes all risks. Recommendations for the use of this product are based on tests we believe to be reliable. The manufacturer and seller are not responsible for results where the product is used under conditions not in strict accordance with our published recommendations and in applications considered suitable for this product. Everkem Diversified Products shall not be responsible for the use of this product in a manner to infringe upon any patent or any other intellectual property rights held by others.

CAUTIONS

KEEP AWAY FROM CHILDREN. Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling. **IF ON SKIN:** Wash with soap and water. Remove contaminated clothing, washing before reuse. If skin irritation occurs: Get medical attention. **IF IN EYES:** Rinse cautiously with water. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **IF INGESTED:** Wash mouth with water. Remove victim to fresh air. Give small quantities of water to drink. Do not induce vomiting. Store locked up. Dispose of contents in accordance with all local, regional, national, and international regulations. **NOT CONSIDERED HAZARDOUS BY OSHA HAZARD COMMUNICATION STANDARD**



WARNING: This product can expose you to chemicals including Crystalline Silica, respirable other than powder, Crystalline Silica, respirable powder, and Titanium Dioxide, which are known to the State of California to cause cancer; and Ethanediol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Everkem Diversified Products
120 Regent Drive | Winston-Salem, NC | 27103
1-800-638-3160 | www.everkemproducts.com

Last Revised: 5/2021