

# Wind-lock Plates

## WIND-DEVILS, ULP-302, ULP-402, LONG LOCK

### MATERIAL SAFETY DATA SHEET

these products do not meet the criteria of hazardous chemicals as defined by the Federal Occupational Safety and Health Communication Standard 29CFR 1910.1200. This form is being provided solely as general information and should not be construed as a determination that the products(s) are hazardous material(s).

### GENERAL INFORMATION

**Manufacturer** Wind-lock Corporation  
1055 Leisz's Bridge Rd.  
Leesport, PA 19533

**Telephone Number** (610) 926-6815

### PRODUCT IDENTIFICATION

**Product Name** Plastic Plates

**Formula** Polyolyfin Resin

### TYPICAL CHEMICAL COMPOSITION

**Components** Polyolyfin resins and various color concentrates

### PHYSICAL DATA

<b><u>Physical State:</u></b>	Solid	<b><u>Specific Gravity:</u></b>	0.88-1.00
<b><u>Appearance:</u></b>	Various Shapes	<b><u>Vapor Pressure: @ 20 C</u></b>	N/A
<b><u>Boiling Point</u></b>	N/A	<b><u>Vapor Density:</u></b>	N/A
<b><u>Melting Point</u></b>	Greater than 149° C (300° F)	<b><u>Evaporation Rate:</u></b>	N/A
<b><u>Solubility in Water:</u></b>	Insoluble	<b><u>% Volatile By Volume:</u></b>	N/A
<b><u>PH:</u></b>	N/A	<b><u>Odor:</u></b>	None

### FIRE AND EXPLOSION HAZARD DATA

**Flammable limits:** N/A

**Flash Point:** > 329° C (625 F) [Setchkin]

**Autoignition Temperature:** > 357° C (675 F) [Setchkin]

**Extinguishing Media:** Water, dry chemical, foam or carbon dioxide

**Special Fire Fighting Procedures:** Standard procedures for Class A fires

**Unusual Fire & Exploding Hazards:** None

# Wind-lock Plates

WIND-DEVILS, ULP-302, ULP-402, LONG LOCK

## REACTIVITY DATA

<b><u>Stability Considerations:</u></b>	Stable
<b><u>Incompatibility:</u></b>	Avoid contact with strong oxidizing agents
<b><u>Hazardous Decomposition Products:</u></b>	None
<b><u>Hazardous Products of Combustion:</u></b>	Carbon Dioxide, Carbon monoxide
<b><u>Hazardous Polymerization:</u></b>	Will not occur

## HEALTH HAZARD DATA

<b><u>Health Effects/Signs &amp; Symptoms:</u></b>	No known hazards
<b><u>Emergency and First Aid Procedures:</u></b>	Molten Resin: If molten material comes into contact with the skin, cool under running stream of water. Do not attempt to remove the resin from the skin, as it could result in severe tissue damage. Get medical attention.
<b><u>Carcinogen Information:</u></b>	None known
<b><u>Eye Contact:</u></b>	Not anticipated to pose a significant hazard
<b><u>Skin Contact:</u></b>	Not anticipated to pose a significant hazard
<b><u>Ingestion:</u></b>	Not anticipated to pose a significant hazard
<b><u>Inhalation:</u></b>	Not anticipated to pose a significant hazard

## OCCUPATIONAL EXPOSURE CONTROL MEASURES

<b><u>Eye Protection:</u></b>	None required, safety glasses recommended
<b><u>Skin Protection:</u></b>	None required, gloves recommended
<b><u>Ingestion:</u></b>	Do not place in mouth

## SPILL, LEAK AND DISPOSAL INFORMATION

<b><u>Procedures to follow if material is released or spilled:</u></b>	N/A
<b><u>Waste Disposal Method:</u></b>	Any excess product can be disposed of by methods which are in accordance with the local, state and federal regulations.

This product is not listed in Federal Hazardous Waste Regulations 40 CFR 261.33, paragraphs (E) or (F), i.e. Chemical Products that are Considered Hazardous if they become wastes.

## APPLICABLE CONTROL MEASURES

<b><u>Handling and Storage Precautions:</u></b>	Keep away from sparks and open flame. This product may react with strong oxidizing agents and should not be stored near such materials. Store in sprinklered warehouse. Keep temperature below 60° C (140° F) for quality control.
---	--